

WHITE-WESTINGHOUSE
WAIP09GNGWM

MODEL		WAIP09GNGWM
TENSIUNE ALIMENTARE	V	220-240
FRECVENTA REȚEA	Hz	50
NUMAR FAZE		1
MOD ALIMENTARE		Interior
CAPACITATE RACIRE FRIGORIFICA	W	2.600
CAPACITATE INCALZIRE FRIGORIFICA	W	2.700
PUTERE CONSUMATA-RACIRE	W	870
PUTERE CONSUMATA-INCALZIRE	W	900
CURRENT ABSORBIT - RACIRE	A	4,00'
CURRENT ABSORBIT - INCALZIRE	A	4,10
PUTERE NOMINALA	W	1400
CURRENT NOMINAL	A	6,2
VOLUM AER CIRCULAT (SH/H/M/L)	mc/h	560/520/440/340
VOLUM DEUMIDIFICARE	l/h	0,8
EFICIENTA ENERGETICA	W/W	3,00
COEFICIENT PERFORMANTA	W/W	3,00
SUPRAFATA ACOPFRITA	mo	12-18
UNITATE INTERIOARA		
TIP VENTILATOR		turbina
DIAMETRU TURBINA (DXL)	mm	092X645
VITEZA ROTATIE RACIRE (SH/H/M/L)	r/min	1260/1070/900/730
VITEZA ROTATIE INCALZIRE (SH/H/M/L)	r/min	1320/1050/980/920
PUTERE MOTOR TURBINA	W	20
RLA MOTOR VENTILATOR	A	0,1
CONDENSATOR MOTOR VENTILATOR	UF	1
MATERIAL EVAPORATOR		Folie aluminiu si teava de cupru
DIAMETRU TEAVA EVAPORATOR	mm	07
DISTANTA INTRE LAMELE	mm	2-1.4
LUNGIME EVAPORATOR (LxAxl)	mm	645x25,4x267
(PUTERE MOTOR BALF. IAJ	W	1
SIGURANTA PRINCIPALA	A	3,15
NIVEL ZGOMOT PRESIUNE (SH/H/M/L)	dB(A)	41/35/31/24
NIVEL ZGOMOT U.I. (SH/H/M/L)	dB(A)	52/46/42/38
DIMENSIUNI U.I. (LxIxA)	mm	912x290x188
GREUTATE NETA U.I.	kg	9
GREUTATE BRUTA U.I.	ka	12
UNITATE EXTERIOARA		
ULEI COMPRESOR		FVC68D/RB68EP
TIP COMPRESOR		Rotary
PUTERE COMPRESOR	W	942
PROTECTIE TERMICA A COMPRESORULUI LA SUPRAINCARCARE		1NT11L-6233
METODA DE CONTROL		valva de expansiune controlata electronic
DOMENIU DE SETARE A TEMPERATURII	°C	16-30
DOMENIU TEMPERATURII AMBIANTE IN MODUL RACIRE	°C	- 7 - 43
DOMENIU TEMPERATURII AMBIANTE IN MODUL INCALZIRE	°C	- 7 - 24
MATERIAL CONDENSATOR		Folie aluminiu si teava de cupru
DIAMETRU TEAVA CONDENSATOR	mm	07
DISTANTA INTRE LAMELE	mm	1-1.4
LUNGIME CONDENSATOR (LxAxl)	mm	730x19x508
VITEZA MOTOR VENTILATOR U.E.	rpm	900/600
PUTERE MOTOR VENTILATOR U.E.	W	30
RLA MOTOR VENTILATOR U.E.	A	0.15
VOLUM AER VEHICULAT (SH/H/M/L)	mc/h	1600
TIP VENTILATORULUI U.E.		axial
DIAMETRUL ELICEI VENTILATORULUI U.E.	mm	0400
METODA DE DEGIVRARE		automat
NIVEL DE ZGOMOT U.E. (HxWxL)	dB(A)	51/-/-
NIVEL DE ZGOMOT LA PUTERE MAXIMA (HxWxL)	dB(A)	61/-/-
DIMENSIUNI U.E. (LxIxA)	mm	776x320x540
GREUTATE NETA U.E.	kg	28
GREUTATEA BRUTA U.E.	kg	31
TIPUL REFRIGERANTULUI		R410A
INCARCARE REFRIGERANT	ka	0.70
TEVI DE LEGATURA		
LUNGIME	m	5
INCARCAREA SUPLIMENTARA CU REFRIGERANT	g/m	20
DIAMETRUL TEVII PENTRU L1CHID	mm	06
DIAMETRUL TEVII PENTRU GAZ	mm	09.52
INALTIMEA MAXIMA DE MONTAJ	m	10
LUNGIMEA MAXIMA A TVII OR	m	15